



Revision Date: 04/06/2017

Version 4.0

SAFETY DATA SHEET

SBR 1686

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Name SBR 1686

SBR CBMB based on 1500 latex and N-330 carbon black

Lion Elastomers
P.O. Box 667
Port Neches, Texas 77651

Customer Service number
Email
Emergency telephone number

1-800-535-9960
Customerservice@lionelastomers.com
CHEMTREC 1-703-527-3887

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: Solid bale, black

WARNING! MAY CAUSE ALLERGIC SKIN REACTION.

Potential Health Effects

Exposure routes

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye contact

May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

Skin contact

Unlikely to cause skin irritation or injury. May cause allergic skin reaction.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Inhalation

Breathing of vapor or mist is possible. It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: Skin, lung (for example, asthma-like conditions)



Revision Date: 04/06/2017

Version 4.0

SAFETY DATA SHEET

SBR 1686

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: irritation (nose, throat, airways), Cough, Exposure to this product (or a component) may cause an allergic reaction (narrowing of the air passages of the lungs resulting in difficult

breathing, tightness in the chest, coughing and wheezing) in some sensitive individuals. Other symptoms of an allergic reaction may include itchy and watery eyes, runny and stuffy nose, sweating, flushing, hives, rapid heart rate, and lowered blood pressure.

Target Organs

No data

Carcinogenicity

Carbon black has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain. It is listed as a carcinogen by The International Agency for Research on Cancer (IARC). Epidemiological studies of the incidence of cancer, cardiovascular or respiratory disease in workers in the carbon black producing industry have shown no significant health effects due to occupational exposure to carbon black.

Reproductive hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

Other information

Prolonged exposure to smoke or fumes generated by heating this product may cause respiratory irritation with throat discomfort, coughing, or breathing difficulty. Repeated exposure may lead to respiratory sensitization (asthma) in susceptible individuals

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components	CAS No.	Concentration
CARBON BLACK	1333-86-4	>=30-<40%
EXTRACTS, PETROLEUM, RESIDUAL OIL SOLVENT	64742-10-5	>=5-<30%
ROSIN, POTASSIUM SALT	61790-50-9	>=1.5-<5%

4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

First Aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.



Revision Date: 03/29/2017

Version 3.1

SAFETY DATA SHEET

1686

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: No information available.

Treatment: No information available.

5. FIREFIGHTING MEASURES

Suitable extinguishing media

Dry chemical, Carbon dioxide (CO₂), Water spray

Hazardous combustion products

carbon dioxide and carbon monoxide. Polymers decompose under fire conditions. The smoke may contain polymer fragments of varying composition and unidentified toxic and/or irritating compounds.

Precautions for fire-fighting

Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

NFPA Flammable and Combustible Liquids Classification

not applicable

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system.



Revision Date: 03/29/2017
Version 3.1

SAFETY DATA SHEET

1686

Methods for cleaning up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Other information

Comply with all applicable federal, state, and local regulations.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

Storage

Store in original container, Store in cool place, Keep away from direct sunlight. Keep at temperatures between 0 and 60°C.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

CARBON BLACK		1333-86-4	
NIOSH	Recommended exposure limit (REL):	0.1 mg/m ³	
NIOSH	Recommended exposure limit (REL):	3.5 mg/m ³	
OSHA Z1	Permissible exposure limit	3.5 mg/m ³	
ACGIH	time weighted average	3 mg/m ³	Inhalable fraction.
EXTRACTS, PETROLEUM, RESIDUAL OIL SOLVENT		64742-10-5	
NIOSH	Recommended exposure limit (REL):	5 mg/m ³	Mist.
NIOSH	Short term exposure limit	10 mg/m ³	Mist.
OSHA Z1	Permissible exposure limit	5 mg/m ³	Mist.
ACGIH	time weighted average	5 mg/m ³	Inhalable fraction.

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the



Revision Date: 03/29/2017

Version 3.1

SAFETY DATA SHEET

1686

responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection

Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Wear resistant gloves (consult your safety equipment supplier).

Discard gloves that show tears, pinholes, or signs of wear.

Respiratory protection

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	solid
Form	bale
Color	black
Odor	characteristic
Flash point	not applicable
Density	1.01 – 1.14 g/cm ³

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to avoid



Revision Date: 03/29/2017

Version 3.1

SAFETY DATA SHEET

1686

excessive heat

Incompatible products

Oxidizing agents

Hazardous decomposition products

carbon dioxide and carbon monoxide

Hazardous reactions

Product will not undergo hazardous polymerization.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin absorption
Skin contact
Eye Contact
Ingestion

Product

Acute oral toxicity : no data available

Acute inhalation toxicity : no data available

Acute dermal toxicity : no data available

Skin corrosion/irritation : no data available

Serious eye damage/eye irritation : no data available

Respiratory or skin sensitisation : no data available

Components:

CARBON BLACK:



Revision Date: 03/29/2017
Version 3.1

SAFETY DATA SHEET

1686

Acute oral toxicity : LD 50 Rat: > 10,000 mg/kg

Acute dermal toxicity : LD 50 Rabbit: > 3 g/kg

EXTRACTS, PETROLEUM, RESIDUAL OIL SOLVENT:

Acute oral toxicity : LD 50 Rat: > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC 50 Rat: > 5 mg/l
Exposure time: 4 h
Method: OECD Test Guideline 403
Aerosol

Acute dermal toxicity : LD 50 Rabbit: > 3,000 mg/kg
Method: OECD Test Guideline 402

Respiratory or skin sensitisation : Test Method: Buehler Test
Species: guinea pig
Result: Did not cause sensitisation on laboratory animals.
Method: OECD Test Guideline 406

ROSIN, POTASSIUM SALT:

Acute oral toxicity : LD 50 Rat: > 2,000 mg/kg
Based on similar product.

Acute dermal toxicity : LD 50 Rat: > 2,000 mg/kg
Based on similar product.

Respiratory or skin sensitisation : Species: mouse
Classification: Did not cause sensitisation on laboratory animals.
Result: Did not cause sensitisation on laboratory animals.
Method: Local lymph node assay

Components:

12. ECOLOGICAL INFORMATION	No data available
-----------------------------------	-------------------

Ecotoxicity

Product:

no data available



Revision Date: 03/29/2017
Version 3.1

SAFETY DATA SHEET

1686

Persistence and degradability

ROSIN, POTASSIUM SALT:

Biodegradability : Biodegradation: 89.5 %
Method: OECD Test Guideline 302B

Bioaccumulative potential

Product:

no data available

Components:

ROSIN, POTASSIUM SALT:

Partition coefficient: n- octanol/water log Pow: 3 - 7

Mobility in soil

Product:

no data available

Components:

no data available

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations.

14. TRANSPORT INFORMATION

REGULATION



Revision Date: 03/29/2017
Version 3.1

SAFETY DATA SHEET

1686

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

U.S. DOT - ROAD

Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TRANSPORT CANADA - ROAD

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

California Prop. 65

WARNING! This product contains a chemical known to the State of

Carbon black



Revision Date: 03/29/2017
Version 3.1

SAFETY DATA SHEET

1686

California to cause cancer.

SARA Hazard Classification
SARA 311/312 Classification
Acute Health Hazard

SARA 313 Component(s)

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Notification status

US. Toxic Substances Control Act	y (positive listing)
Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)	y (positive listing)
Australia. Industrial Chemical (Notification and Assessment) Act	y (positive listing)
Japan. ENCS - Existing and New Chemical Substances Inventory	n (negative listing)
Korea. Toxic Chemical Control Law (TCCL) List	y (positive listing)
Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act	y (positive listing)
China. Inventory of Existing Chemical Substances	y (positive listing)

	HMIS	NFPA
Health	2	1
Flammability	1	1
Physical hazards	0	
Instability		0
Specific Hazard	--	--

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index



Revision Date: 03/29/2017

Version 3.1

SAFETY DATA SHEET

1686

CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
DOT : Department of Transportation
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
HMIRC : Hazardous Materials Information Review Commission
HMIS : Hazardous Materials Identification System
NFPA : National Fire Protection Association
NIOSH : National Institute for Occupational Safety and Health
OSHA : Occupational Safety and Health Administration
PMRA : Health Canada Pest Management Regulatory Agency
RTK : Right to Know
WHMIS : Workplace Hazardous Materials Information System